

search user exit in trans

```
*&-----*  
*& Report ZUSEREXIT *  
*& *  
*&-----*  
*& *  
*& *  
*&-----*
```

REPORT ZUSEREXIT.

TABLES : tstc, tadir, modsapt, modact, trdir,

tfdir, enlfdir, tstct.

DATA : jtab LIKE tadir OCCURS 0 WITH HEADER LINE.

DATA : field1(30).

DATA : v_devclass LIKE tadir-devclass.

PARAMETERS : p_tcode LIKE tstc-tcode OBLIGATORY.

SELECT SINGLE * FROM tstc WHERE tcode EQ p_tcode.

IF sy-subrc EQ 0.

SELECT SINGLE * FROM tadir WHERE pgmid = 'R3TR'

AND object = 'PROG'

AND obj_name = tstc-pgmna.

MOVE : tadir-devclass TO v_devclass.

IF sy-subrc NE 0.

SELECT SINGLE * FROM trdir WHERE name = tstc-pgmna.

IF trdir-subc EQ 'F'.

SELECT SINGLE * FROM tfdir WHERE pname = tstc-pgmna.

SELECT SINGLE * FROM enlfdir WHERE funcname = tfdir-funcname.

SELECT SINGLE * FROM tadir WHERE pgmid = 'R3TR'

AND object = 'FUGR'

```
                search user exit in trans
AND obj_name EQ enlfdir-area.
```

```
MOVE : tadir-devclass TO v_devclass.
```

```
ENDIF.
```

```
ENDIF.
```

```
SELECT * FROM tadir INTO TABLE jtab WHERE pgmid = 'R3TR'
```

```
        AND object = 'SMOD'
```

```
        AND devclass = v_devclass.
```

```
SELECT SINGLE * FROM tstct WHERE sprsl EQ sy-langu
```

```
        AND tcode EQ p_tcode.
```

```
FORMAT COLOR COL_POSITIVE INTENSIFIED OFF.
```

```
WRITE: / (19) 'Transaction Code - ',
```

```
        20(20) p_tcode,
```

```
        45(50) tstct-ttext.
```

```
SKIP.
```

```
IF NOT jtab[] IS INITIAL.
```

```
WRITE: / (95) sy-uline.
```

```
FORMAT COLOR COL_HEADING INTENSIFIED ON.
```

```
WRITE: /1 sy-vline,
```

```
        2 'Exit Name',
```

```
        21 sy-vline ,
```

```
        22 'Description',
```

```
        95 sy-vline.
```

```
WRITE: / (95) sy-uline.
```

```
LOOP AT jtab.
```

```
SELECT SINGLE * FROM modsapt WHERE sprsl = sy-langu AND
```

```
        name = jtab-obj_name.
```

```
FORMAT COLOR COL_NORMAL INTENSIFIED OFF.
```

search user exit in trans

```
WRITE: /1 sy-vline,  
      2 jtab-obj_name HOTSPOT ON,  
      21 sy-vline ,  
      22 modsapt-modtext,  
      95 sy-vline.
```

ENDLOOP.

```
WRITE: /(95) sy-uline.
```

```
DESCRIBE TABLE jtab.
```

SKIP.

```
FORMAT COLOR COL_TOTAL INTENSIFIED ON.
```

```
WRITE: / 'No of Exits: ' , sy-tfill.
```

ELSE.

```
FORMAT COLOR COL_NEGATIVE INTENSIFIED ON.
```

```
WRITE: /(95) 'No User Exit exists'.
```

ENDIF.

ELSE.

```
FORMAT COLOR COL_NEGATIVE INTENSIFIED ON.
```

```
WRITE: /(95) 'Transaction Code Does Not Exist'.
```

ENDIF.

AT LINE-SELECTION.

```
GET CURSOR FIELD field1.
```

```
CHECK field1(4) EQ 'JTAB'.
```

```
SET PARAMETER ID 'MON' FIELD sy-lisel+1(10).
```

```
CALL TRANSACTION 'SMOD' AND SKIP FIRST SCREEN.
```